

SCRUBBER DRIERS - WALK BEHIND

## CT5

MAX PRODUCTIVITY

900 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

75 min.

WATER TANK  
RUNNING TIME

25 min.  
working session

 ECO SELECT

 LI-ION  
BATTERY

 RDS  
REVERSE DRY SYSTEM



### INNOVATIONS



RDS  
REVERSE  
DRY  
SYSTEM



ANC™  
ADVANCED  
NOISE  
CONTROL



SLS™  
SELF  
LEVELING  
SYSTEM



ECO  
SELECT



LI-ION  
LITHIUM  
BATTERY

### SPEC



CT5 CAN BE STORED, TRANSPORTED AND PARKED IN EVERY SPACE IN JUST FEW SECONDS.



RECHARGEABLE LITHIUM-ION BATTERY BOTH ON BOARD THE MACHINE AND EXTERNALLY



THE RDS ALLOWS TO WASH AND DRY EASILY EVEN IN POINTS WHERE OTHER MACHINES DO NOT REACH

## MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



## TECHNICAL DATA

CT5 B28

### PERFORMANCE

Max theoretical productivity	m <sup>2</sup> /h	900
Cleaning path	mm	280
Water tank capacity (solution recovery)	l	5 - 5
Max running time	min	75
Voltage	V	36
Installed power	W	220
Brush pressure	kg	12
Squeegee width	mm	300
Max speed	km/h	3.5
Weight	kg	20.2
Dimension (LxWxH)	mm	758 x 376 x 392

## CONSUMABLES

### BRUSHES



SPPV02580 | POLYPROPYLENE (PP) SOFT BRUSH  
 SPPV02438 | POLYPROPYLENE (PP) MEDIUM BRUSH  
 SPPV02581 | POLYPROPYLENE (PP) HARD BRUSH

### PADS (BOX OF 5)



SPPV02583 | 11" POLISH PAD - WHITE  
 SPPV02584 | 11" BUFF PAD - RED  
 SPPV02585 | 11" MEDIUM DUTY PAD - GREEN  
 SPPV02586 | 11" STRIPPING PAD - BROWN  
 SPPV02582 | PAD DRIVER

### SQUEEGEE BLADES



KTRI06090 | LATEX BLADE  
 KTRI06092 | LINATEX BLADE