

SCRUBBER DRIERS - WALK BEHIND

CT40PA

MAX PRODUCTIVITY

1750 m²/h

BATTERIES
RUNNING TIME

2,5 h

WATER TANK
RUNNING TIME

45 min
working session



INNOVATIONS



DBL™
DOUBLE
BATTERY
LIFE




SLS™
SELF
LEVELING
SYSTEM

SPECS



INTUITIVE CONTROL PANEL



ANTI-FOAM SYSTEM WITH
SPECIAL ELECTROMECHANICAL
SUCTION MOTOR PROTECTION

MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



MUNICIPALITIES

TECHNICAL DATA

Code	CT40 BT50
PERFORMANCE	
Max theoretical productivity	1750 m ² /h
Cleaning path	500 mm
Water tank capacity (solution recovery)	40/50 l
Max running time	150 min
Voltage	24(2x12)-105 GEL V-Ah
Installed power	1030 W
Brush pressure	18 kg
Squeegee width	815 mm
Max speed	3,5 km/h
Weight	67 kg
Dimension (LxWxH)	1230 x 516 x 960 mm

CONSUMABLES (Codes available on price list)

BRUSHES




SPPV01498 | POLYPROPYLENE (PP) BRUSH

PADS



L-17260 | 20' POLISH PAD - WHITE
 L-17261 | 20' BUFF PAD - RED
 L-17262 | 20' SCRUB PAD - BLUE
 L-1243339 | 20' BUFF PAD - RED (BOX OF 5)
 L-1243352 | 20' POLISH PAD - WHITE (BOX OF 5)

SQUEEGEE BLADES



MPVR08039 | LATEX FRONT BLADE
 MPVR08035 | LATEX REAR BLADE