

Therm 895-1

TOP
SELLER



Tidy storage system
Practical stowing of the trigger gun with safety catch and lances

Integrated Hose drum
Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

Digital operating panel
to control the water temperature and view cold/hot use operating time management

Removable covers
Protect the mechanical components from environmental factors and provide convenient access

Cleaning Agent Intake
Injector system for dispensing of cleaning agents

Parking brake
For a secure stationary position



Water output < 1000 l/h **therm 895-1**

Technical specifications		Three Phase
Operating pressure adjustable	psi	2830
Max. admissible overpressure	psi	3120
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12
Motor speed	Rpm	1400
Water output	l/min l/h	14.9 895
kW		5.5
Volume water tank	l	4
Hot water output adjustable	°C	12-86
Steam level	°C	155
Heating output	kW	65
Fuel tank	l	35
Power supply cable	m	7.5
Dimensions L x W x H	mm	1050 / 800 / 1000
Weight	kg	220
Detergent Injector		●
Equipment		
Hose drum		●
Steel braided high-pressure hose	m	20
Trigger gun with safety catch	Model	Starlet
Stainless steel lance with flat jet nozzle	Nozzle size	● D25045

2 YEAR
COMMERCIAL
WARRANTY

Brass
Pump Head
10 YEAR
WARRANTY



TECHNICAL HIGHLIGHTS!

DIGITAL THERMOSTAT

The high-pressure cleaners of the therm-1-series are fitted with a digital thermostat which combines a variety of advantages in operation and service.

- Intelligent system analysis
- Reduction of fuel costs thanks to object-specific temperature specification
- Simple reading of the operating hours

Dial a Demo
0300 387 678

